






























50HZ

Marine Diesel Generator Powered by Cummins | Three Phase Specifications:(37.5KVA-1250KVA)

Genset Model	ESP		PRP		Consumption (L/h)	L*W*H(mm)	Engine Power (KW)	Engine Model	Country of origin	Cyl Arrangement	Displacement (L)	Bore x Stroke (mm)	Cooling
	KVA	KW	KVA	KW									
KGCM38	41.8	33	38	30	6.39	1650*850*1270	47	4BTA3.9-GM47		4L	3.9	102 x 102	Water
KGCM50	55	44	50	40	10.02	1740*850*1270	47	4BTA3.9-GM47		4L	3.9	102 x 102	Water
KGCM63	69.3	55	63	50	12.47	1900*890*1300	83	6BT5.9-GM83		6L	5.9	102 x 120	Water
KGCM80	88	70.4	80	64	15.96	1900*890*1300	83	6BT5.9-GM83		6L	5.9	102 x 120	Water
KGCM94	103	82.5	94	75	18.71	1920*890*1300	100	6BT5.9-GM83		6L	5.9	102 x 120	Water
KGCM113	124	99	113	90	22.45	1990*890*1300	100	6BT5.9-GM100		6L	5.9	102 x 120	Water
KGCM125	138	110	125	100	24.94	2110*860*1360	115	6CT8.3-GM115		6L	8.3	114 x 135	Water
KGCM150	165	132	150	120	29.93	2110*860*1360	155	6CTA8.3-GM155		6L	8.3	114 x 135	Water
KGCM188	207	165	188	150	31.8	2210*860*1400	200	6LTAA8.9-GM200		6L	8.9	114 x 145	Water
KGCM225	248	198	225	180	38.16	2210*860*1400	200	6LTAA8.9-GM200		6L	8.9	114 x 145	Water
KGCM250	275	220	250	200	48.94	2760*990*1790	240	NTA855-DM		6L	14	140 x 152	Water
KGCM250	275	220	250	200	48.94	2760*990*1790	240	N855-DM		6L	14	140 x 152	Water
KGCM313	344	275	313	250	61.18	2760*990*1790	284	NTA855-DM		6L	14	140 x 152	Water
KGCM313	344	275	313	250	61.18	2760*990*1790	284	N855-DM		6L	14	140 x 152	Water
KGCM350	385	308	350	280	68.52	2990*990*1790	317	NTA855-DM		6L	14	140 x 152	Water
KGCM350	385	308	350	280	68.52	2990*990*1790	317	N855-DM		6L	14	140 x 152	Water
KGCM375	413	330	375	300	44.8	3170*1000*1900	336	KTA19-DM		6L	19	159 x 159	Water
KGCM400	440	352	400	320	49.5	3170*1000*1900	358	K19-DM		6L	19	159 x 159	Water
KGCM438	482	385	438	350	49.5	3170*1000*1900	403	KTA19-DM		6L	19	159 x 159	Water
KGCM438	482	385	438	350	49.5	3170*1000*1900	410	K19-DM		6L	19	159 x 159	Water
KGCM500	550	440	500	400	54.2	3170*1000*1900	448	KTA19-DM		6L	19	159 x 159	Water
KGCM500	550	440	500	400	54.2	3170*1000*1900	448	K19-DM		6L	19	159 x 159	Water
KGCM625	688	550	625	500	78.5	3950*1500*2500	560	KT38-DM		12V	38	159 x 159	Water
KGCM750	825	660	750	600	87.5	4050*1400*2680	664	KTA38-DM		12V	38	159 x 159	Water
KGCM813	894	715	813	650	78.5	4050*1400*2680	746	KTA38-DM		12V	38	159 x 159	Water
KGCM875	963	770	875	700	103.7	4100*1500*2500	814	K38-DM		12V	38	159 x 159	Water
KGCM1000	1100	880	1000	800	109.4	4100*1500*2500	880	KTA38-DM		12V	38	159 x 159	Water
KGCM1000	1100	880	1000	800	109.4	4100*1500*2500	880	K38-DM		12V	38	159 x 159	Water
KGCM1250	1375	1100	1250	1000	141.7	4250*1500*2500	1092	K50-DM		12V	38	159 x 159	Water