


















50HZ

Diesel Generator Powered by Vman | Three Phase Specifications:(300KVA-1125KVA)

Genset Model	ESP		PRP		Consumption g/kw.h	Open L*W*H(mm)	Silent L*W*H(mm)	Engine Model	Country of origin	Cyl Arrangement	Displacement (L)	Lube oil(L)	Cooling
	KVA	KW	KVA	KW									
KG300	330	264	300	240	192	2500*1500*1300	4000*1700*2000	D11A2		6L	10.964	25	Water
KG313	344	275	313	250	192	2500*1500*1300	4000*1700*2000	D11A1		6L	10.964	25	Water
KG350	385	308	350	280	192	2550*1500*1300	4000*1700*2000	D11A		6L	10.964	25	Water
KG375	413	330	375	300	192	2600*1500*1400	4000*1700*2000	D11		6L	10.964	25	Water
KG400	440	352	400	320	196	2800*1500*1400	4300*2100*2300	D15A2		8V	14.618	27	Water
KG438	482	385	438	350	198	2820*1500*1500	4300*2100*2300	D15A1		8V	14.618	27	Water
KG500	550	440	500	400	200	2820*1500*1550	4300*2100*2300	D15A		8V	14.618	27	Water
KG550	605	484	550	440	200	2850*1500*1550	4700*2100*2450	D15		8V	14.618	27	Water
KG563	619	495	563	450	192	3000*1500*1600	4700*2100*2450	D22A3		12V	21.927	57	Water
KG625	688	550	625	500	192	3200*1500*1600	4700*2100*2450	D22A2		12V	21.927	57	Water
KG688	757	605	688	550	192	3370*1500*1700	6000*2300*2800	D22A		12V	21.927	57	Water
KG750	825	660	750	600	192	3500*1500*1700	6000*2300*2800	D22		12V	21.927	57	Water
KG800	880	704	800	640	192	3500*1500*1700	6000*2300*2800	D22Z		12V	21.927	57	Water
KG875	963	770	875	700	197	4000*1400*2000	6000*2300*2800	D30A3		16V	29.235	78	Water
KG1000	1100	880	1000	800	197	4000*1600*2000	6000*2300*2800	D30A2		16V	29.235	78	Water
KG1063	1169	935	1063	850	197	4300*1700*2100	6000*2300*2800	D30A1		16V	29.235	78	Water
KG1125	1238	990	1125	900	197	4300*1850*2200	6000*2300*2800	D30A		16V	29.235	78	Water