

50HZ

Diesel Generator Powered by Perkins | Three Phase
Specifications:(9KVA-2250KVA)

Genset Model	ESP		PRP		Fuel Cons L/H(75%)	Open L*W*H(mm)	Silent L*W*H(mm)	Engine Model	Country of origin	Cyl Arrangement	Displacement (L)	Gov	Cooling
	KVA	KW	KVA	KW									
KGP9	10	8	9	7.2	2.3	1140*550*1020	1870*730*1136	403A-11G1		3L	1.131	M	Water
KGP13	15	12	13	10	2.8	1450*550*1190	2067*905*1281	403A-15G1		3L	1.5	M	Water
KGP15	16.5	13	15	12	3.1	1450*550*1190	2067*905*1281	403A-15G2		3L	1.496	M	Water
KGP20	22	18	20	16	4	1660*550*1255	2067*905*1281	404A-22G1		4L	2.216	M	Water
KGP30	33	26	30	24	5.4	1915*750*1410	2220*1005*1315	1103A-33G		3L	3.3	M	Water
KGP45	50	40	45	36	8.2	1915*750*1410	2590*1005*1396	1103A-33TG1		3L	3.3	M	Water
KGP60	66	53	60	48	10.4	1920*750*1410	2590*1005*1296	1103A-33TG2		3L	3.3	M	Water
KGP65	72	58	65	52	11.2	2180*800*1375	2700*1100*1632	1104A-44TG1		4L	4.4	M	Water
KGP80	88	70	80	64	14	2180*800*1375	2700*1100*1632	1104A-44TG2		4L	4.4	M	Water
KGP100	110	88	100	80	17.1	2165*830*1290	2800*1100*1701	1104C-44TAG2		4L	4.4	E	Water
KGP135	150	120	135	108	22.7	2590*800*1550	3400*1100*1972	1106A-70TG1		6L	7.01	M	Water
KGP150	165	132	150	120	24.7	2575*830*1345	3600*1100*2170	1106A-70TAG2		6L	7.01	M	Water
KGP180	200	160	180	144	31.8	2763*890*1375	3600*1100*2170	1106A-70TAG3		6L	7.01	M	Water
KGP200	220	176	200	160	34.7	2763*890*1375	3600*1100*2170	1106A-70TAG4		6L	7.01	E	Water
KGP225	250	200	225	180	35.7	2845*1030*1495	4120*1250*2207	1506A-E88TAG2		6L	8.8	ECM	Water
KGP250	275	220	250	200	41.6	2975*1098*1665	4120*1130*2207	1506A-E88TAG3		6L	8.8	ECM	Water
KGP275	300	240	275	220	45.8	2975*1098*1665	4120*1130*2207	1506A-E88TAG4		6L	8.8	ECM	Water
KGP300	330	264	300	240	48	2975*1098*1610	4265*1400*2240	1506A-E88TAG5		6L	8.8	ECM	Water
KGP350	400	320	350	280	54	3180*1180*1930	4400*1400*2525	2206C-E13TAG2		6L	12.5	ECM	Water
KGP400	450	360	400	320	62	3180*1180*1930	4400*1400*2525	2206C-E13TAG3		6L	12.5	ECM	Water
KGP450	500	400	450	360	72	3450*1260*1955	4750*1400*2415	2506C-E15TAG1		6L	15.2	ECM	Water
KGP500	550	440	500	400	76	3450*1260*1955	4750*1450*2415	2506C-E15TAG2		6L	15.2	ECM	Water
KGP600	660	528	600	480	90	3600*1540*2170	4750*1800*2490	2806C-E18TAG1A		6L	18.13	ECM	Water
KGP650	715	572	650	520	97	3600*1540*2170	4750*1800*2490	2806A-E18TAG2		6L	18.13	ECM	Water
KGP750	825	660	750	600	122	3800*1750*2230	ISO 20ft container	4006-23TAG2A		6L	22.921	E	Water
KGP800	880	704	800	640	130	4600*2000*2365	5612*2140*2500	4006-23TAG3A		6L	22.921	E	Water
KGP900	1000	800	900	720	143	4700*2050*2210	ISO 20ft container	4008TAG1A		8L	30.561	E	Water
KGP1000	1100	880	1000	800	163	4700*2050*2210	5900*2240*2505	4008TAG2A		8L	30.561	E	Water
KGP1125	1250	1000	1125	900	188	4830*2050*2190	ISO 20ft container	4008-30TAG3		8L	30.561	E	Water
KGP1250	1375	1100	1250	1000	196	4830*2195*2425	ISO 20ft container	4012-46TWG0A		12V	45.842	E	Water
KGP1350	1500	1200	1350	1080	213	4920*2010*2520	ISO 20ft container	4012-46TWG3A		12V	45.842	E	Water
KGP1500	1650	1320	1500	1200	201	4920*2170*2530	ISO 20ft container	4012-46TAG2A		12V	45.842	E	Water
KGP1650	1850	1480	1650	1320	275	4920*2170*2530	ISO 20ft container	4012-46TAG23A		12V	45.842	E	Water
KGP1705	1875	1500	1705	1364	275	4920*2170*2530	ISO 20ft container	4012-46TAG23A		12V	45.842	E	Water
KGP1845	2030	1624	1845	1476	277	5962*2128*2522	ISO 20ft container	4016TAG1A		16V	61.123	E	Water
KGP2050	2260	1808	2050	1640	316	5962*2128*2522	ISO 40ft container	4016TAG2A		16V	61.123	E	Water
KGP2250	2500	2000	2250	1800	346	6265*2210*3040	ISO 40ft container	4016-61TRG3		16V	61.123	E	Water