


















50HZ

Diesel Generator Powered by Vman | Three Phase Specifications:(300KVA-1125KVA)

Genset Model	ESP		PRP		Consumption g/kw.h	Open L*W*H(mm)	Silent L*W*H(mm)	Engine Model	Country of origin	Cyl Arrangement	Displacement (L)	Lube oil(L)	Cooling
	KVA	KW	KVA	KW									
KG300	330	264	300	240	191	3000*1200*1800	4000*1700*2000	DE11A260		6L	10.964	25	Water
KG325	358	275	325	250	191	3000*1200*1800	4300*2100*2300	DE11A400		6L	10.964	25	Water
KG350	385	308	350	280	191	3000*1200*1800	4300*2100*2300	DE11A420		6L	10.964	25	Water
KG400	440	330	400	300	196	3300*1250*1840	4300*2100*2300	DE15A500		8V	14.618	27	Water
KG450	495	352	450	320	196	3300*1250*1840	4700*2100*2450	DE15A560		8V	14.618	27	Water
KG500	550	385	500	350	196	3000*1250*1840	4700*2100*2450	DE15A610		8V	14.618	27	Water
KG563	619	440	563	400	196	3000*1250*1840	4700*2100*2450	DE15A660		8V	14.618	27	Water
KG563	619	484	563	440	192	3500*1400*1890	4700*2100*2450	DE22A690		12V	21.927	57	Water
KG625	688	495	625	450	192	3500*1400*1890	4700*2100*2450	DE22A750		12V	21.927	57	Water
KG625	688	550	625	500	192	3500*1400*1890	4700*2100*2450	DE22A780		12V	21.927	57	Water
KG688	757	605	688	550	192	3500*1400*1890	4700*2100*2450	DE22A840		12V	21.927	57	Water
KG750	825	660	750	600	192	3500*1400*1890	6000*2300*2800	DE22A950		12V	21.927	57	Water
KG800	880	704	800	640	192	3800*1400*1890	6000*2300*2800	DE22A990		12V	21.927	57	Water
KG875	963	770	875	700	195	4240*1850*2250	6000*2300*2800	DE30A1080		16V	29.235	78	Water
KG1000	1100	880	1000	800	195	4240*1850*2250	6000*2300*2800	DE30A1220		16V	29.235	78	Water
KG1063	1169	935	1063	850	195	4240*1850*2250	6000*2300*2800	DE30A1320		16V	29.235	78	Water
KG1125	1238	990	1125	900	195	4240*1850*2250	6000*2300*2800	DE30A1400		16V	29.235	78	Water