

















50HZ

Diesel Generator Powered by Weichai | Three Phase Specifications:(500KVA-2750KVA)

Genset Model	ESP		PRP		Consumption g/kw.h	Open L*W*H(mm)	Silent L*W*H(mm)	Engine Model	Country of origin	Cyl Arrangement	Displacement (L)	Lube oil(L)	Cooling
	KVA	KW	KVA	KW									
KGW500	550	440	500	400	205	3000*1000*1850	4700*2100*2450	WP13d440E310		6L	12.54	36	Water
KGW625	688	550	625	500	210	3600*1500*1850	4700*2100*2450	6M33D572E310		6L	19.6	61	Water
KGW688	757	605	688	550	205	3600*1500*1900	4700*2100*2450	6M33D633E310		6L	19.6	61	Water
KGW800	880	704	800	640	197	3650*1500*1900	6000*2300*2800	6M33D725E310		6L	19.6	61	Water
KGW1125	1238	990	1125	900	197	4600*1900*2300	6000*2300*2800	12M33D968E310		12V	39.2	146	Water
KGW1250	1375	1100	1250	1000	199	4800*2000*2350	6000*2300*2800	12M33D1108E310		12V	39.2	146	Water
KGW1375	1513	1210	1375	1100	200	4800*2000*2350	REQ	12M33D1240E310		12V	39.2	146	Water
KGW1500	1650	1320	1500	1200	200	4800*2050*2450	REQ	12M33D1320E310		12V	39.2	146	Water
KGW1650	1815	1452	1650	1320	214	5200*2500*2700	REQ	16M33D1530E310		16V	52.3	171	Water
KGW1750	1925	1540	1750	1400	215	5200*2500*2700	REQ	16M33D1580E310		16V	52.3	171	Water
KGW1875	2063	1650	1875	1500	216	5200*2500*2700	REQ	16M33D1680E310		16V	52.3	171	Water
KGW2000	2200	1760	2000	1600	205	5200*2500*2700	REQ	16M33D1800E310		16V	52.36	171	Water
KGW2000	2200	1760	2000	1600	198	6100*2350*2800	REQ	12M55D1870E310		12V	65.65	480	Water
KGW2250	2475	1980	2250	1800	199	6100*2350*2800	REQ	12M55D2020E310		12V	65.65	480	Water
KGW2500	2750	2200	2500	2000	202	6100*2350*2800	REQ	12M55D2210E310		12V	65.65	480	Water
KGW2750	3025	2420	2750	2200	203	6100*2350*2800	REQ	12M55D2450E310		12V	65.65	480	Water