


























50HZ

Diesel Generator Power by Googol | Three Phase Specifications:(450KVA-3250KVA)

Genset Model	ESP		PRP		Consumption g/kw.h	Open L*W*H(mm)	Silent L*W*H(mm)	Engine Model	Country of origin	Cyl Arrangement	Displacement (L)	Lube oil(L)	Cooling
	KVA	KW	KVA	KW									
KGQ450	495	396	450	360	200	3000*1050*1430	4300*2100*2300	PTAA780G1		6L	12.8	40	Water
KGQ500	550	440	500	400	200	3150*1050*1430	4700*2100*2450	PTAA780G3		6L	12.8	40	Water
KGQ550	605	484	550	440	200	3150*1050*1430	4700*2100*2450	PTAA780G5		6L	12.8	40	Water
KGQ688	757	605	688	550	203	3230*1400*2050	4700*2100*2450	PTAA1120G3		10V	18.2	34	Water
KGQ750	825	660	750	600	199	3700*1400*2050	4700*2100*2450	PTAA1340G3		12V	21.9	36	Water
KGQ800	880	704	800	640	199	3800*1600*2100	4850*2150*2550	PTAA1340G5		12V	21.9	36	Water
KGQ1000	1100	880	1000	800	199	4500*1800*2100	6000*2300*2800	PTAA1780G5		16V	29.2	48	Water
KGQ1100	1210	968	1100	880	198	4500*1800*2100	REQ	PTAA1780G7		16V	29.2	48	Water
KGQ1250	1375	1100	1250	1000	199	5000*2100*2500	REQ	PTAA2230G1		20V	36.5	60	Water
KGQ1375	1513	1210	1375	1100	199	5000*2100*2600	REQ	PTAA2230G3		20V	36.5	60	Water
KGQ1650	1815	1452	1650	1320	194	5230*2220*2600	REQ	QTA3240G5		12V	53.1	180	Water
KGQ1875	2063	1650	1875	1500	194	5350*2200*2750	REQ	QTA3240G7		12V	53.1	180	Water
KGQ2063	2269	1815	2063	1650	194	5800*2220*2750	REQ	QTA3240G9		12V	53.1	180	Water
KGQ2250	2475	1980	2250	1800	194	5900*2500*2800	REQ	QTAA4320G3		16V	70.8	240	Water
KGQ2500	2750	2200	2500	2000	194	5950*2850*2800	REQ	QTAA4320G5		16V	70.8	240	Water
KGQ2750	3025	2420	2750	2200	194	6000*2560*2900	REQ	QTAA4320G7		16V	70.8	240	Water
KGQ2250	2475	1980	2250	1800	194	6000*2560*2900	REQ	QTA4320G3		16V	70.8	240	Water
KGQ2500	2750	2200	2500	2000	194	6050*2610*2920	REQ	QTA4320G5		16V	70.8	240	Water
KGQ2750	3025	2420	2750	2200	194	6100*2650*3000	REQ	QTA4320G7		16V	70.8	240	Water
KGQ2750	3025	2420	2750	2200	195	8100*3470*3850	REQ	QTAA5400G1		20V	88.5	300	Water
KGQ3000	3300	2640	3000	2400	194	8100*3470*3850	REQ	QTAA5400G3		20V	88.5	300	Water
KGQ3250	3575	2860	3250	2600	195	8100*3470*3850	REQ	QTAA5400G5		20V	88.5	300	Water
KGQ2750	3025	2420	2750	2200	195	8100*3470*3850	REQ	QTA5400G1		20V	88.5	300	Water
KGQ3000	3300	2640	3000	2400	193	8100*3470*3850	REQ	QTA5400G3		20V	88.5	300	Water
KGQ3250	3575	2860	3250	2600	193	8100*3470*3850	REQ	QTA5400G5		20V	88.5	300	Water