























50HZ

Diesel Generator Powered by FAWDE | Three Phase Specifications:(14.4KVA-360KVA)

Genset Model	ESP		PRP		Consumption (g/Kw.h)	Open L*W*H(mm)	Silent L*W*H(mm)	Engine Model	Country of origin	Cyl Arrangement	Displacement (L)	Bore x Stroke (mm)	Cooling
	KVA	KW	KVA	KW									
KGF14	15	13	14	12	240	1300*700*1050	2100*850*1100	4DW81-23D		4L	2.27	85 x 100	Water
KGF19	21	18	19	16	240	1350*700*1050	2100*850*1100	4DW91-29D		4L	2.54	90 x 100	Water
KGF20	26	22	24	20	220	1450*700*1050	2100*850*1100	4DW92-35D		4L	2.54	90 x 100	Water
KGF24	32	26	29	24	216	1450*700*1050	2100*850*1100	4DW92-39D		4L	2.54	90 x 100	Water
KGF29-II	32	26	29	24	216	1600*700*1050	2100*850*1100	4DW93-42D		4L	2.54	90 x 100	Water
KGF30	33	28	30	25	230	1550*760*1050	2100*850*1100	4DX21-45D		4L	3.86	102 x 118	Water
KGF38	42	35	38	32	230	1650*760*1050	2300*950*1200	4DX21-53D		4L	3.86	102 x 118	Water
KGF36	40	33	36	30	220	1650*760*1050	2300*950*1200	4DX22-50D		4L	3.86	102 x 118	Water
KGF48	53	44	48	40	220	1800*760*1150	2400*950*1200	4DX22-65D		4L	3.86	102 x 118	Water
KGF45	50	42	45	38	215	2100*850*1400	2400*950*1200	4DX23-65D		4L	3.86	102 x 118	Water
KGF58	64	53	58	48	215	2100*850*1400	2400*950*1200	4DX22-78D		4L	3.86	102 x 118	Water
KGF66	73	61	66	55	215	2100*850*1400	2500*950*1300	4110/125Z-09D		4L	4.75	110 x 125	Water
KGF87	96	79	87	72	205	2100*850*1400	2500*950*1300	CA4F2-12D		4L	4.75	110 x 125	Water
KGF96	106	88	96	80	202	2550*950*1550	3400*1100*1650	6CDF2D-14D		6L	6.55	110 x 115	Water
KGF120	132	110	120	100	202	2550*950*1550	3400*1100*1650	CA6DF2-17D		6L	7.13	110 x 125	Water
KGF144	158	132	144	120	200	2550*950*1550	3400*1100*1650	CA6DF2-19D		6L	7.13	110 x 125	Water
KGF180	198	165	180	150	196	2750*1050*1650	3400*1100*1650	CA6DL1-24D		6L	7.7	110 x 135	Water
KGF216	238	198	216	180	195	2750*1050*1650	3800*1100*1850	CA6DL2-27D		6L	8.57	110 x 145	Water
KGF240	264	220	240	200	195	2750*1050*1650	3800*1100*1850	CA6DL2-30D		6L	8.57	112 x 148	Water
KGF300	330	275	300	250	189	3050*1250*1700	3400*1100*1650	CA6DM2J-39D		6L	11.04	123 x 155	Water
KGF324	356	297	324	270	189	3200*1250*1900	4100*1500*1850	CA6DM2J-41D		6L	11.04	123 x 155	Water
KGF360	396	330	360	300	191	3200*1250*1900	4300*1500*1850	CA6DN1J-45D		6L	12.53	131 x 155	Water