

















50HZ

Diesel Generator Powered by Yangdong | Three Phase Specifications:(10KVA-60KVA)

Genset Model	ESP		PRP		Consumption 100% Load L/h	Open L*W*H(mm)	Silent L*W*H(mm)	Engine Model	Country of origin	Cyl Arrangement	Displacement (L)	Bore x Stroke (mm)	Cooling
	KVA	KW	KVA	KW									
KGG10	11	8.8	10	8	3.3	1200*700*980	1900*820*1000	YD380D		3L	1.357	80 x 90	Water
KGG10	11	8.8	10	8	3.3	1200*700*980	1900*820*1000	YD385D		3L	1.532	85 x 90	Water
KGG13	14.3	11	13	10	4.1	1300*700*980	1900*820*1000	YD480D		4L	1.809	80 x 90	Water
KGG15	16.5	13.2	15	12	5	1350*700*980	1900*820*1000	YD4KD		4L	1.809	80 x 90	Water
KGG16	17.6	14.3	16	13	5.4	1400*750*980	2000*870*1000	YND485D		4L	2.156	85 x 95	Water
KGG19	20.9	16.5	19	15	6.2	1400*750*980	2050*870*1000	YND490D		4L	2.54	90 x 100	Water
KGG20	22	17.6	20	16	6.6	1400*750*1020	2050*870*1000	YSD490D		4L	2.67	90 x 105	Water
KGG23	25.3	19.8	23	18	7.4	1400*750*1020	2050*870*1000	Y490D		4L	2.67	90 x 105	Water
KGG24	26.4	22	24	20	8	1500*750*12020	2050*870*1000	Y495D		4L	2.997	95 x 105	Water
KGG25	27.5	22	25	20	8.3	1600*750*1050	2250*930*1150	Y4100D		4L	3.707	100 x 118	Water
KGG30	33	26.4	30	24	9.9	1600*750*1050	2250*930*1150	Y4102D		4L	3.875	102 x 118	Water
KGG38	41.8	33	38	30	12.4	1700*750*1100	2250*930*1150	Y4105D		4L	4.1	105 x 118	Water
KGG38	41.8	33	38	30	12.4	1700*750*1100	2300*930*1150	Y4102ZD		4L	3.875	102 x 118	Water
KGG45	49.5	39.6	45	36	14.9	1800*800*1050	2300*930*1150	Y4102ZLD		4L	3.875	102 x 118	Water
KGG50	55	44	50	40	16.5	1800*800*1050	2300*930*1150	Y4105ZLD		4L	4.1	105 x 118	Water
KGG60	66	52.8	60	48	19.8	1900*800*1050	2300*930*1150	YD4EZLD		4L	4.1	105 x 118	Water